R1400CH

Chemical Kit







Features

- Half face respirator (R1400)
- 1 pair of ABEK1P3 R D R filters
- 1 pair of pre-filter holders
- 1 pack of 10 pre-filters
- ▲ 4x multi-wipes

Standards & Certification

Force360 recognise that without product certification by a Notified Body all product performance testing, and adherence to standards claims cannot be independently verified. If they are not as claimed, serious safety implications for the wearer, and legal implications for the supplier and the employer may arise.

Force360 source their entire range of reusable respiratory protection from a single manufacturing partner to ensure consistency and reliability of product, but most importantly Force360 have taken the further step of engaging a globally recognised Notified Body to audit and certify both the manufacturing process and the products.

All of Force360's respiratory protection is certified to the latest AS/NZS respiratory protection standards.





Specifications

Part No. R1400CH

Protection ABEK1P3 R D Filter

Usage Reusable

Sizing

R1400CH.S Small R1400CH.M Medium R1400CH.L Large

Packaging









R1400CH

R1100 - Filter Range - Technical Specifications

Usage		P3 R	A1	A2	ABE1	ABEK1	A1P3 R D	A2P3 R D	ABE1P3 R D	ABEK1P3 R D
Filter Class		P3	Class 1	Class 2	Class 1	Class 1	Class 1 P3	Class 2 P3	Class 1 P3	Class 1 P3
Organic Vapours	А	N/A	1	1	1	1	1	1	1	1
Inorganic Vapours			N/A		J	1	N	/A	1	1
Acidic Vapours	Е		N/A		J	1	N/A		1	1
Ammonia Vapours	K		N/A			1	N/A			✓
Nuisance Odours		N/A	1	1	1	1	1	J	1	✓
Dusts	Р	1		N	/A		,	J	1	1
Mists		1		N	I/A		7	1	1	1
Water Based Painting		1	N/A			J	J	1	1	
Solvent Based Brush Paint	ting	N/A	1	1	1	1	1	J	1	1
Rubbing Down Paint		1	N/A			1	1	1	1	
Paint Stripping, Chemical or Heat			N/A			1	1	1	1	
White Spirit		N/A	1	1	1	1	1	1	1	1
Chlorine (Cleaning & Pools	5)		N/A J J		1	N/A		1	1	
Glyphosate (Weed Killer)		1	N/A				1	1	1	1
Brick Acid (Graffiti Removal)			N/A			1	N	/A	1	4
Formaldehyde			N/A 🗸			1		N/A		1
Fibres & Fibre Glass	lass 🗸 N		I/A		1	1	1	4		
Plaster		1	✓ N/A		I/A		1	1	1	1
Silica (Concrete / Stone Cutting)		N/A			1	1	1	4		
Woods (Hard & Soft)		N/A			1	1	1	1		
MDF (Machine Tooling)		1				I/A			1	1
Welding (Ferrous & Lead)		1	N/A J J					1	4	
Earth Moving (Contaminated)			N/A						1	

		Particulate Only Filter		Gas On	ly Filter			Comi	oined Filter	
EN Requirement		P3 R	A1	A2	ABE1	ABEK1	A1P3 R D	A2P3 R D	ABE1P3 R D	ABEK1P3 R D
Filter Class		P3	Class 1	Class 2	Class 1	Class 1	Class 1 P3	Class 2 P3	Class 1 P3	Class 1 P3
	Actual	125g	210g	210g	230g	230g	250g	250g	280g	280g
Weight per filter pair	EN140	< 300g								
	EN136		< 500g							
Pressure Drop	Actual	0.9 mbar	0.9 mbar	1.2 mbar	1.0 mbar	1.0 mbar	1.7 mbar	1.9 mbar	1.8 mbar	1.8 mbar
(Measurement at 95L/min)	EN	4.2 mbar	4.0 mbar	5.6 mbar	4.0 mbar	4.0 mbar	8.2 mbar	9.8 mbar	8.2 mbar	8.2 mbar
Efficiency	Actual	> 99.99%	N/A			> 99.99%				
Lillololloy	EN	> 99.95%	N/A			> 99.95%				
Penetration	Actual	< 0.01%	N/A				< 0.01%			
reneuation	EN	< 0.05%	N/A			< 0.05%				
Cyclohexane	Actual	N/A	200 min	50 min	150 min	150 min	200 min	50 min	150 min	150 min
Oydiolickalic	EN	N/A	70 min	35 min	70 min	70 min	70 min	35 min	70 min	70 min
Hydrogen Cyanide	Actual		N/A				N/A		>100 min	
nyurogen oyamuc	EN		N/A		25 min		N/A		25 min	
Hydrogen Sulphide	Actual		N/A		>100 min		N/A		>100 min	
nyurogen ourpmue	EN	N/A			40 min	40 min	N/A		40 min	40 min
Chlorine	Actual		N/A				N/A		>100 min	
Olloring	EN		N/A		20 min	20 min	N/A		20 min	20 min
Sulphur Dioxide	Actual		N/A		65 min	50 min	N/A		65 min	50 min
Odipilai Dioxide	EN		N/A		20 min	20 min	N/A		20 min	20 min
Ammonia	Actual		N	/A		90 min	N/A			90 min
Allinonia	EN		N	/A		50 min	N/A		50 min	

Workplace Exposure Level - This table is for reference purposes only. A proper risk assessment by qualified personnel should be carried out before selecting an appropriate filter cartridge

R1400CH

Particulate Filters

Particulate filters capture particulates in the air such as dusts, mists and fumes. They do not protect the user against gases or vapors. Particulate filters are classified into three groups, relative to the particulate size filtration capacity and toxicity of the particulate.

Class P1 Filters

P1 filters protect against mechanically generated particles. P1 filters are available as the powered type, replaceable filter type and disposable type.

Class P2 Filters

P2 filters protect against mechanically or thermally generated particles (or both). P2 filters are available as the powered type, replaceable filter type and disposable type.

Class P3 Filters

P3 filters are to protect against highly toxic or irritant particles. P3 filters are available as the powered type and replaceable filter type.

To achieve P3 filter classification a full-face piece is required (for non-powered air), or a head covering or full face piece for a Powered Air Purifying Respirator (PAPR). **Note:** When a P3 filter is used in conjunction with a half face piece, the protection level is equivalent to a P2 filter.

Disposable respirators / dust masks are particulate filters, usually P1 or P2. They cover the mouth and nose and protect the wearer against airborne contaminants including dust, mists, liquids and some fumes, but not gases or vapors.

Dust masks are not suitable where:

- Contaminant concentrations are dangerous to life or health, unknown or exceed the relevant exposure standard
- Toxic gases or vapours are present
- A satisfactory fit of the mask is not obtained due to facial hair or other characteristics that prevent a good seal between the edge of the mask and the wearer's face.
- ▲ If the atmosphere is deficient in oxygen, a confined space or poorly ventilated area
- If there is a smell or taste of a contaminant and/or if persons in the area experience nose and/or throat irritation – some dust masks do have an active carbon layer added to reduce nuisance levels of organic vapours that can create unpleasant smells

Class	Efficiency	Penetration	Application
P1	80% (Particles to $1\mu m$ micron = $0.001mm$ size)	Not more than 20%	Dust
P2	94% (Particles to 0.3µm micron = 0.0003mm size)	Not more than 6%	Toxic dusts, including welding fumes and asbestos
Р3	99.95% (Particles to <0.3µm micron = less than 0.0003mm size)	Not more than 0.05%	Toxic dusts including asbestos, welding fumes (Only achieved with PAPR or Full Face)

Gas Filters

Classes for gas filters are distinguished by how much gas they're able to absorb. Gas filters are classified by one of the following classes:

Class AUS

Low absorption capacity filters

Low to medium absorption capacity filters

Class 2

Medium absorption capacity filters

High absorption capacity filters

Gas and particle filters also use a colour coded system for identification. Multiple colours represent filter type protection:

A Organic Vapours (boiling point >65°C)

AX Organic Vapours (boiling point <65°C)

B Inorganic Gases

E Acid Gases

K Ammonia

Combination Filters

Combination filters are used when gases/vapours occur simultaneously with particles, e.g. in high pressure cleaning, spray painting, heating substances or gas condensation. Select an appropriate combination filter from the Corpro range when subject to this environment.

Hq

Mercury

Protection Factors

Depending on the combination of cartridge/filter and respirator, different levels of protection may be achieved. The Protection Factor is the reduction in exposure expected with correct use of a respirator. e.g. A protection factor of 10 means the wearer can expect a 10 times reduction in exposure to the airborne concentration of contaminants.

As per the table below - the higher the protection factor, the greater the reduction in exposure to airborne contaminants for the wearer.

Particulate Protection

Respirator	Filter	Protection Factor
Half Face Respirator	P2 Filter	Up to 10
Half Face Respirator	P3 Filter	Up to 10
Full Face Respirator	P2 Filter	Up to 50
Full Face Respirator	P3 Filter	Up to 100

Gas/Vapour Protection

Respirator	Filter	Protection Factor
Half Face Respirator	Class 1	Up to 10
Half Face Respirator	Class 2	Up to 10
Full Face Respirator	Class 1	Up to 50
Full Face Respirator	Class 2	Up to 100