Airless Pty Ltd

# Material Safety Data Sheet

Issue Date: June 2017

# ISSUED by Airless Pty Ltd

Product Name: ATOMEX PISTON LUBE

Not classified as hazardous according to criteria of NOHSC

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY

Product Name ATOMEX PISTON LUBRICANT Product Code P/N AX/PL05 Product Use Lubrication of Piston Airless Sprayers (packing seals) **Company Name** Airless Pty Ltd (ABN 97 121 334 987) **Address** 29 Carlingford Street Regents Park NSW 2143 **Emergency Telephone:** (02) 9644 1040 **Telephone Number/Fax** Tel: (02) 9644 1040 Fax: (02) 9644 3147

## 2. COMPOSITION/INFORMATION ON INGREDIENTS Information on Composition

Severely refined petroleum distillates with performance additives.

#### **Ingredients Name**

Ingredients determined not to be hazardous

# CAS

Not required

Proportion 100 %

#### **3. HAZARDS IDENTIFICATION**

Not classified as hazardous according to NOHSC criteria. Not classified as a dangerous good according to the ADG Code. Risk Phrases Not applicable Safety Phrases Not applicable

## 4. FIRST AID MEASURES

## Inhalation

Remove the source of contamination or move the victim to fresh air. Ensure airways are clear and have qualified person give oxygen through a facemask if breathing is difficult. If irritation develops and persists, seek medical attention.

## Ingestion

DO NOT induce vomiting. Immediately wash out mouth with water. Seek medical attention.

## Skin

Remove contaminated clothing. Wash gently and thoroughly with water and non-abrasive soap. Ensure contaminated clothing is washed before re-use or discard. If irritation develops, seek medical attention.

## Eye

If contact with the eye(s) occurs, wash with copious amounts of water, holding eyelids(s) open. Take care not to rinse contaminated water into the non-effected eye. If irritation develops and persists, seek medical attention.

## **First Aid Facilities**

Eye wash and normal washroom facilities.

## **Advice to Doctor**

Treat symptomatically.

## 5. FIRE FIGHTING MEASURES

#### **Extinguishing Media**

Carbon dioxide, foam or dry chemical. Do NOT use water jets. Cool fire exposed containers with water spray.

#### **Specific Hazards**

Combustible C2 liquid. Fire-exposed container may rupture/explode.

## Hazardous

#### Combustion Products

Under fire conditions this product may emit toxic and/or irritating fumes including oxides of carbon.

# Precautions in

#### connection with Fire

Self-Contained Breathing Apparatus (S.C.B.A) and full protective clothing should be worn to minimise exposure

## 6. ACCIDENTAL RELEASE MEASURES

Remove all sources of ignition. Increase ventilation. Evacuate all unnecessary personnel. Wear full protective equipment and clothing to minimise exposure. If possible contain the spill. Place inert, non combustible, absorbent material onto spillage. Use clean non-sparking tools to collect the material and place into a suitable labelled container. If large quantities of this material enter the waterways contact the Environmental Protection Authority, or your local Waste Management Authority.

## 7. HANDLING AND STORAGE

#### Corrosiveness

Not corrosive to aluminium.

#### Handling

Repeated or prolonged contact with this material should be avoided in order to lessen the possibility of skin disorders. It is essential that all who come into contact with this material maintain high standards of personal hygiene ie. washing hands prior to eating, drinking or going to the toilet. Build-up of mists in the working atmosphere must be prevented. Misuse of empty containers can be hazardous. Do not cut, weld, heat or drill containers. Residue may ignite with explosive violence if heated sufficiently. Do not pressurise or expose to open flame or heat. Keep container closed and bung in place.

#### Storage

Combustible C2 liquid for storage and handling purposes. Store in a cool, dry, well-ventilated area, out of direct sunlight. Avoid sparks, flames, and other ignition sources. Store away from incompatible materials such as materials that support combustion (oxidising materials). Reference should be made to Australian Standard AS1940- The storage and handling of flammable and combustible liquids.

## 8. EXPOSURE CONTROLS, PERSONAL PROTECTION

#### Exposure Limits

No exposure standards have been established for this material by the National Occupational Health And Safety Commission (NOHSC).

## Respiratory

#### Protection

If engineering controls are not effective in controlling airborne exposure then respiratory protective equipment should be used suitable for protecting against airborne contaminants. Final choice of appropriate breathing protection is dependent upon actual airborne concentrations and the type of breathing protection required will vary according to individual circumstances. Expert advice may be required to make this decision. Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices.

## **Eye Protection**

Safety glasses with side shields, goggles or full-face shield as appropriate recommended. Final choice of appropriate eye/face protection will vary according to individual circumstances i.e. methods of handling or engineering controls and according to risk assessments undertaken. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.

## **Hand Protection**

Wear gloves of impervious material. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

## **Body Protection**

Wear appropriate clothing including chemical resistant apron where clothing is likely to be contaminated. It is advisable that a local supplier of personal protective clothing is consulted regarding the choice of material.

## **Eng. Controls**

Natural ventilation should be sufficient, however where vapours or mists are generated the use of a local exhaust ventilation system (drawing vapours/mists away from workers breathing zone) is recommended.

## **Other Information**

No biological limit allocated.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Amber coloured oily liquid.

Melting Point Not available.

**Boiling Point** Not available.

Solubility in Water

Insoluble

**Specific Gravity** (H20=1) 0.880 @ 15 C

**pH Value** Not applicable

Vapour Pressure Not applicable

Vapour Density (Air=1) Not applicable

Flash Point 215 C (Penskey Martens Closed Cup)

## Flammability

Classified as a Class C2 (COMBUSTIBLE LIQUID) for the purpose of storage and handling, in accordance with the requirements of AS1940. Remove all sources of heat and ignition.

**Ignition Temperature** Not available.

Flammable Limits LEL Not available.

Flammable Limits UEL Not available.

**Kinematic Viscosity** 

32 cSt @ 40 C 5.4 cSt @ 100 C

**10. STABILITY AND REACTIVITY** 

Stability Stable under normal conditions.

Hazardous Polymerization Will not occur.

Materials to Avoid Strong oxidising agents

Hazardous Decomposition Products

Thermal decomposition may result in the release of toxic and/or irritating fumes including carbon monoxide and carbon dioxide.

Hazardous Reaction Hazardous reaction with strong oxidising agents.

**Conditions to Avoid** Heat, direct sunlight, open flames or other sources of ignition.

## **11. TOXICOLOGICAL INFORMATION**

**Toxicology Information** No toxicity data is available for this material.

Inhalation

May cause irritation to the mucous membrane and upper airways, where material is heated and is used in poorly ventilated areas. Symptoms may include headache, dizziness and nausea.

## Ingestion

May cause irritation of the gastrointestinal system. Symptoms may include nausea, vomiting and diarrhoea.

## Skin

May cause irritation in contact with the skin, which may result in redness and itchiness, possibly leading to dermatitis.

## Eye

May cause irritation in contact with the eyes which could result in redness, stinging and tearing.

#### **Chronic Effects**

Prolonged or repeated contact with this material may result in skin irritation possibly leading to dermatitis.

#### **12. ECOLOGICAL INFORMATION**

No ecological data is available for this material.

#### **Environ. Protection**

Prevent this material from entering the environment.

#### Mobility

No data available for this specific product.

Persistence / Degradability

No data available for this specific product.

#### Bioaccumulation

No data available for this specific product.

**Ecotoxicity** No data available for this specific product.

## **13. DISPOSAL CONSIDERATIONS**

Dispose of waste according to federal, E.P.A. and state regulations. Assure conformity with all applicable regulations.

#### **14. TRANSPORT INFORMATION**

Not classified as a Dangerous Good according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.

#### U.N. Number None Allocated

Proper Shipping Name None Allocated DG

Class None Allocated

Hazchem Code None Allocated

## Packing Group

None Allocated

## **15.REGULATORY INFORMATION**

Poisons Schedule Not Scheduled

## **16.OTHER INFORMATION**

Contact Person/Point For information concerning details on this Safety Data Sheet contact your local Technical Services Manager on the following number:- (02) 9644 1040

## IMPORTANT DISCLAIMER

All reasonable care has been taken to ensure that the information and advice contained herein are accurate at the time of printing. However, Airless Pty Ltd accepts no tortious or contractual liability for any loss or damages suffered as a consequence of reliance on the information and advice contained herein. EMERGENCY CONTACT (02) 9644 1040

## **SDS History**

MSDS Creation: August 2010

... End Of MSDS ...