



# 5 Port Manifold Connector Push Fitting

**\$17.31**  
**INCL. GST**

## Product Images



## Short Description

5 Port Manifold Connector Push Fitting can be used for air, liquids and some inert gases. Push-in air line fittings allow fast connection and disconnection for compressed air circuits eliminating the need for tools.

## Description

---

Push-in fittings are used for connecting polyurethane or nylon tubing mostly in compressed air circuits but can also be used for some liquids and inert gas.

Rated to 150psi maximum working pressure and constructed of composite plastic, brass with stainless steel locking ring.

Push-in fittings require no tools when connecting or disconnecting tubing, simply push the tube into the fitting and it's locked into position. To remove the tube simply push the blue collar down back towards the fitting and pull the tube away.

### 5 Port Manifold Connector Push Fittings are available in the following sizes -

4mm x 5 Port Manifold Push Fit	Part No. AX/12-SPW4
6mm x 5 Port Manifold Push Fit	Part No. AX/12-SPW6
8mm x 5 Port Manifold Push Fit	Part No. AX/12-SPW8
10mm x 5 Port Manifold Push Fit	Part No. AX/12-SPW10
12mm x 5 Port Manifold Push Fit	Part No. AX/12-SPW12

We keep all of these push fit sizes in stock, orders placed before 3.00pm Monday-Friday will be despatched the same day by express courier.

We also stock polyurethane & nylon air/fluid hosing by the meter and in rolls with delivery Australia wide.

## Additional Information

---

Brands	Atomex
--------	--------

## Additional Options

---

<b>Choose a push fitting size</b>	4mm x 5 Port Manifold Push Fit	\$0.00
	6mm x 5 Port Manifold Push Fit	\$1.94
	8mm x 5 Port Manifold Push Fit	\$4.85
	10mm x 5 Port Manifold Push Fit	\$13.86
	12mm x 5 Port Manifold Push Fit	\$20.79

