



Atomex ATFP 1" Compressed Air Filter Type C

\$210.60
INCL. GST

Product Images





Short Description

Atomex AFTP 1" Compressed Air Filter Type C is used as a pre-filter before an air dryer to reduce particles and emulsion down to a 5 micron. Replaceable filters and large bowl surface area will reduce pressure drop while removing impurities from compressed air.

Description

Atomex ATFP 1" Compressed Air Filters utilise an advanced bowl design with a large tapered surface area which will reduce pressure drop while removing impurities from your compressed air supply. Filters are interchangeable between models and easily identified by the colour and mesh pattern.

Atomex ATFP Compressed air filters include 3/8" stainless steel ball valve and stainless steel reducing nipple that are fitted to the 1/2" drain port at the bottom of the bowl. All filters can be fitted with the optional SCP (Part No. AX/09-117-000) automatic mechanical drain system which replaces the manual ball valve.

Atomex offer four types of compressed air treatment filters to ensure the highest quality air to meet your requirements.

Atomex ATFP Type C

- Part No. AX/09-115-02C
- Designed as a pre-filter for inlet of air dryers
- Primary function to remove excess water & emulsion
- 5 Micron filtration for particle, water & emulsion
- 1"BSP Inlet & Outlet Port
- Replaceable Filter Element (Part No. AX/09-116-02C)
- Includes 3/8" stainless steel ball valve for draining
- Optional SCP automatic drain (Part No. AX/09-117-000)

Atomex ATFP Type T

- Part No. AX/09-115-02T
- Designed as a post-filter for outlet of air dryers
- Primary function to remove oil & small particles
- 0.01 Micron filtration for residual oil and small particles
- 1"BSP Inlet & Outlet Port
- Replaceable Filter Element (Part No. AX/09-116-02T)
- Includes 3/8" stainless steel ball valve for draining

Atomex ATFP Type A

- Part No. AX/09-115-02A
- Designed as a post-filter for outlet of air dryers
- Primary function to remove dust, liquid oil
- 1 Micron filtration for residual oil and small particles
- 1"BSP Inlet & Outlet Port
- Replaceable Filter Element (Part No. AX/09-116-02A)
- Includes 3/8" stainless steel ball valve for draining

Atomex ATFP Type H

- Part No. AX/09-115-02H
- Designed as a post-filter for outlet of air dryers
- Primary function to remove oil vapour & odour
- 0.003 Micron filtration for residual oil vapour & odour
- 1"BSP Inlet & Outlet Port
- Replaceable Filter Element (Part No. AX/09-116-02H)
- Includes 3/8" stainless steel ball valve for draining

Atomex AFTP filter elements should be changed at least every 12 months or as required to keep your compressed air quality at it's best.

AA Spray stock a full range of compressed air water separation tanks, compressed air refrigerated dryers and compressed air treatment filters with fast delivery Australia wide.

Additional Information

Brands	Atomex
--------	--------

Additional Options

Add an SCP Automatic Condensate Drain	No, thanks.	\$0.00
	SCP HAD20B Automatic Condensate Drain 1/2"	\$40.00

