



# Atomex ATFP Replacement Filter Elements

**\$74.53**  
**INCL. GST**

## Product Images



Type C Filter Element



Type T Filter Element



Type A Filter Element



## Type H Filter Element



### Short Description

---

Atomex ATFP Replacement Filter Elements should be replaced every 12 months or as required. Available in Type C, T, A & H filter elements these are interchangeable between all Atomex ATFP 1" Compressed Air Filters.

## Description

---

Atomex offer four types of compressed air treatment filters to ensure the highest quality air to meet your requirements.

### Atomex ATFP Type C

- Part No. AX/09-115-02C
- Designed as a pre-filter for inlet of air dryers
- Primary function to remove excess water & emulsion
- 5 Micron filtration for particle, water & emulsion
- 1" BSP Inlet & Outlet Port
- Replaceable Filter Element (Part No. AX/09-116-02C)
- Includes 3/8" stainless steel ball valve for draining
- Optional SCP automatic drain (Part No. AX/09-117-000)

### Atomex ATFP Type T

- Part No. AX/09-115-02T
- Designed as a post-filter for outlet of air dryers
- Primary function to remove oil & small particles
- 0.01 Micron filtration for residual oil and small particles
- 1" BSP Inlet & Outlet Port
- Replaceable Filter Element (Part No. AX/09-116-02T)
- Includes 3/8" stainless steel ball valve for draining

### Atomex ATFP Type A

- Part No. AX/09-115-02A
- Designed as a post-filter for outlet of air dryers
- Primary function to remove dust, liquid oil
- 1 Micron filtration for residual oil and small particles
- 1" BSP Inlet & Outlet Port
- Replaceable Filter Element (Part No. AX/09-116-02A)
- Includes 3/8" stainless steel ball valve for draining

### Atomex ATFP Type H

- Part No. AX/09-115-02H
- Designed as a post-filter for outlet of air dryers
- Primary function to remove oil vapour & odour
- 0.003 Micron filtration for residual oil vapour & odour
- 1" BSP Inlet & Outlet Port
- Replaceable Filter Element (Part No. AX/09-116-02H)
- Includes 3/8" stainless steel ball valve for draining

Atomex ATFP filter elements should be changed at least every 12 months or as required to keep your compressed air quality at it's best.

AA Spray stock a full range of compressed air water separation tanks, compressed air refrigerated dryers and compressed air treatment filters with fast delivery Australia wide.

## Additional Information

---

Brands	Atomex
--------	--------

## Additional Options

---

<b>Choose Filter Type</b>	Type C Filter Element	\$0.00
	Type T Filter Element	\$0.00
	Type A Filter Element	\$0.00
	Type H Filter Element	\$0.00

