



Atomex RD-42 Refrigerated Compressed Air Dryer 50cfm

\$2,905.66
INCL. GST

Product Images



Optional Atomex ATP Type C Pre-Filter
with SCP Automatic Drain Fitted



Short Description

Atomex RD-42 Refrigerated Compressed Air Dryer offers efficient and economical removal of excess water in compressed air either in the liquid or vapour phase.

Description

Atomex refrigerated air dryers are designed to remove condensate from compressed air systems and will work on standard 10amp 240 volt power. We recommend the use of a Pre-Filter with minimum 5 micron filtration fitted to the inlet of the air dryer to ensure maximum efficiency.

Atomex RD-42 Refrigerated Compressed Air Dryer feature -

- 50cfm (1189Litres/Per Minute) Capacity
- 1" BSP Inlet & Outlets
- Adjustable timed automatic drain valve
- Includes 2m of drain tube
- Fully automatic system
- No settings or start up procedure required
- Works on standard 240v power

Atomex Refrigerated Air Dryers are available in three models -

- Atomex RD-22 30cfm Refrigerated Air Dryer 1" Port
- Atomex RD-42 50cfm Refrigerated Air Dryer 1" Port
- Atomex RD-82 75cfm Refrigerated Air Dryer 1" Port

Refrigerated Air Dryer Hints -

- Refrigerated air dryers should be positioned between the air receiver and the inlet of your compressed air pipe system.
- Pre-filter should be fitted to the air dryer inlet to reduce condensate.
- Refrigerated air dryers should be at least 1m from any walls to allow for ventilation.
- The area should be free from dust and contamination that may gather in the cooling elements or compressor.
- Ensure the location is easily accessible for maintenance.
- All hoses that feed compressed air both in and out of the refrigerator air dryer should be crimped and of the same internal diameter of the ports.
- Weekly maintenance should include dusting out the cooling elements, checking the auto-drain valve filter and testing the drain valve function.
- Switch the air dryer off when not in use.

Optional Pre-Filter For Left Side Fit Includes -

- 1 x Atomex ATFP Compressed Air Filter Type C
- 1 x SCP HAD20B Automatic Condensate Drain Valve
- 1 x 2m 8mm tube for condensate drain
- 1 x 1" BSP Male Nipple for air inlet on filter
- 1 x 1" Male - Male Pipe 400mm

Optional Pre-Filter For Right Side Fit Includes -

- 1 x Atomex ATFP Compressed Air Filter Type C
- 1 x SCP HAD20B Automatic Condensate Drain Valve
- 1 x 2m 8mm tube for condensate drain
- 1 x 1" BSP Male Nipple for air inlet on filter
- 1 x 1" Male - Male Pipe 400mm

AA Spray stock a full range of compressed air water separation tanks, compressed air refrigerated dryers and compressed air treatment filters with fast delivery Australia wide.

Additional Information

Brands	Atomex
--------	--------

Additional Options

Optional Pre-Filter (Recommended)	No, thanks	\$0.00
	Left Side Fitted Pre-Filter with Automatic Drain	\$235.00
	Right Side Fitted Pre-Filter with Automatic Drain	\$235.00

