



# DeVilbiss PROLite-S Gravity Touch Up Spray Gun TE5 Air Cap

Regular Price

**\$858.00** Special  
Price

**\$579.15**

**INCL. GST**

## Product Images



**DEVILBISS**

## Short Description

The DeVilbiss PROLite-S is a professional touch up and spot repair gravity spray delivering controlled high-performance atomisation for repair applications such as bumper bars, wheels and spot repairs.



# PROLite<sup>S</sup>

The PROLite-S is famous for exceptional handling, delicate trigger control and the ability to blend solid colours — particularly metallics and special effect colours — over a small area. Combining the fit, feel and balance of the renowned PROLite with the compact dimensions essential in a spot repair gun, minor repairs can be completed to full warranty standards quickly and efficiently with minimal paint, all while maintaining pinpoint colour accuracy.

Specifically designed and precision engineered to ensure perfect atomization of all the latest waterborne and solventborne coatings, the PROLite-S is available with a range of high efficiency and HVLP setups. Each is developed specifically to provide versatility for the most popular automotive refinish materials.

The lightweight forged aluminium gun body of the PROLite-S is designed to provide the fit, feel and balance essential to achieve a perfect SMART or Micro repair. The compact front end provides optimum visibility of the fan pattern even when working in restricted spaces. The heavy duty anodized finish of the PROLite-S is designed to provide the durability needed in today's high throughput body shops.

### **The DeVilbiss PROLite-S touch up gravity gun features –**

- Lightweight and precision-engineered trigger action ensuring excellent control for superb feathering
- Comprehensive range of air cap, fluid nozzle and needle combinations for atomization of all types of waterborne and solventborne materials
- Renowned DeVilbiss fit, feel and balance is ensured by the ergonomically designed anodized, forged aluminium gun body
- Combines the performance and durability of a full-size gun with lightweight pinpoint delivery for spot repairs

### **The DeVilbiss PROLite-S offers three air cap configurations –**

#### **TE5 - High Efficiency**

- General purpose air cap can be used with basecoats & clearcoats
- Air consumption 100 l/min (3.5cfm)
- Recommended air inlet pressure 29psi (2.0 Bar)
- Typical fan pattern width 180mm @ 50-100mm distance
- Nozzle sizes available – 0.8, 1.0, 1.2 & 1.4mm

#### **HV5 - HVLP**

- HVLP air cap can be used with basecoats & clearcoats
- Air consumption 135l/min (4.8cfm)
- Recommended air inlet pressure 29psi (2.0 Bar)
- Typical fan pattern width 160mm @ 50-100mm distance
- Nozzle sizes available – 0.8, 1.0, 1.2 & 1.4mm

#### **MC1 –High Efficiency**

- Micro air cap can be used with basecoats & clearcoats

- Air consumption 50l/min (1.8cfm)
- Recommended air inlet pressure 14.5psi (1.0 Bar)
- Typical fan pattern width 25mm @ 50-100mm distance
- Nozzle sizes available – 0.6mm

[View the full range of DeVilbiss PROLite-S Gravity Touch Up Spray Guns available](#)

## Additional Information

Brands	DeVilbiss
--------	-----------

## Additional Options

<b>Choose Nozzle Size</b>	0.8mm	\$0.00
	1.0mm	\$0.00
	1.2mm	\$0.00
	1.4mm	\$0.00

